

Web Development

Produced
by

Eamonn de Leastar (edeleastar@wit.ie)

Department of Computing, Maths & Physics
Waterford Institute of Technology

<http://www.wit.ie>

<http://elearning.wit.ie>





Waterford Institute of Technology
INSTITIÚID TEICNEOLAÍOCHTA PHORT LÁIRCE



Lab10 Exercises

HTTP Request/Response Cycle





Exercise 1

- Change the Profile controller/view to display the currently logged in users full name (not just the first name).

```
public class Profile extends Controller
{
    public static void index()
    {
        String userId = session.get("logged_in_userid");
        User user = User.findById(Long.parseLong(userId));
        String name = user.firstName;
        render(name);
    }
    //...
}
```

controllers/Profile.java

```
...
    <h2>${name}'s Profile</h2>
...
```

views/Profile/index.html

Exercise 1: Solution

```
public class Profile extends Controller
{
    public static void index()
    {
        String userId = session.get("logged_in_userid");
        User user = User.findById(Long.parseLong(userId));
        render(user);
    }
    //...
}
```

controllers/Profile.java

```
...
<h2>${user.firstName}
    ${user.lastName}'s Profile</h2>
...
```

views/Profile/index.html

Exercise 2

- In the user Profile view, see if you can figure out how to let the user see his/her email.

```
...  
<h2 class="ui header">${user.firstName} ${user.lastName}'s Profile </h2>  
...
```

views/Profile/index.html

Exercise 2: Solution


```
...  
<h2 class="ui header">${user.firstName} ${user.lastName}'s Profile (${user.email})</h2>  
...
```

views/Profile/index.html

Exercise 4

- Currently, every time we stop the application our database is cleared - and when we run again we have to register new users again. This can get tiresome and repetitive.
- Our framework comes with a simple mechanism for pre-loading our database if we want to hit the ground running with initial test data

Exercise 4: Solution



```
import java.util.List;

import play.*;
import play.jobs.*;
import play.test.*;

import models.*;

@OnApplicationStart
public class Bootstrap extends Job
{
    public void doJob()
    {
        Fixtures.deleteDatabase();
        Fixtures.loadModels("data.yml");
    }
}
```


Exercise 4: Solution

```
import java.util.List;

import play.*;
import play.jobs.*;
import play.test.*;

import models.*;


@OnApplicationStart
public class Bootstrap extends Job
{
    public void doJob()
    {
        Fixtures.deleteDatabase();
        Fixtures.loadModels("data.yml");
    }
}
```



```
User(homer):
  firstName: Homer
  lastName: Simpson
  email: homer@simpson.com
  password: secret

User(marge):
  firstName: Marge
  lastName: Simpson
  email: marge@simpson.com
  password: secret
```

- On startup, database populated with these users



Except where otherwise noted, this content is licensed under a Creative Commons Attribution-NonCommercial 3.0 License.

For more information, please see <http://creativecommons.org/licenses/by-nc/3.0/>

